

WORM-DRIVE HOSE CLAMP

4-PIECE HEAVY DUTY QUADRA-LOCK CONSTRUCTION PROVIDES STRENGTH AND STABILITY
CONICAL ARCHED PERFORATED SLOTS:

MORE STEEL BETWEEN PERFORATIONS FOR ADDED STRENGTH
AND SMOOTHER WORM-DRIVE ENGAGEMENT

1/4" SLOTTED HEX SCREW (410 STAINLESS STEEL)
ON CLAMPS WITH 5/16" WIDE BAND
5/16" SLOTTED HEX SCREW (410 STAINLESS STEEL)
ON CLAMPS WITH 1/2" & 9/16" WIDE BANDS

300 SERIES STAINLESS BAND
0.023" THICK BAND

PER SAE STANDARD J1508 TYPE "F" & "M"
MADE IN THE USA BY 



SAE SIZE	EFFECTIVE DIAMETER RANGE		5/16" BAND WIDTH	1/2" BAND WIDTH	9/16" BAND WIDTH
	MIN	MAX	PART #	PART #	PART #
4	7/32"	5/8"	3604		
6	7/16"	25/32"	3606	64006H	200 06 H
8	1/2"	29/32"		64008H	200 08 H
10	9/16"	1-1/16"		64010H	200 10 H
12	11/16"	1-1/4"		64012H	200 12 H
16	13/16"	1-1/2"		64016H	200 16 H
20	13/16"	1-3/4"		64020H	200 20 H
24	1-1/16"	2"		64024H	200 24 H
28	1-5/16"	2-1/4"		64028H	200 28 H
32	1-9/16"	2-1/2"		64032H	200 32 H
36	1-13/16"	2-3/4"		64036H	200 36 H
40	2-1/16"	3"		64040H	200 40 H
44	2-5/16"	3-1/4"		64044H	200 44 H
48	2-9/16"	3-1/2"		64048H	200 48 H
52	2-13/16"	3-3/4"		64052H	200 52 H
56	3-1/16"	4"		64056H	200 56 H
64	3-9/16"	4-1/2"		64064H	200 64 H
72	1-7/8"	5"		64072H	200 72 H
80	2-1/2"	5-1/2"		64080H	200 80 H
88	3-1/8"	6"		64088H	200 88 H
96	3-5/8"	6-1/2"		64096H	200 96 H
104	4-1/8"	7"		64104H	200 104 H
128	5-5/8"	8-1/2"			200 128 H
152	7-1/8"	10"			200 152 H
188	9-3/8"	12-1/4"			200 188 H
212	10-7/8"	13-3/4"			200 212 H